

# 32' OUTLAW FORCE-FEED TRAILER

## UNBEATABLE VALUE MEETS HIGH- PERFORMANCE

The 32' Outlaw Force-Feed Trailer is a heavy-duty, high-performance manure handling solution designed to maximize efficiency at the right value.

- 15" or 18" Bazooka Farmstar submersible pump
- 8-inch plumbing
- 32' boom reach
- Gooseneck or bumper hitch trailer



## FEATURES

### HIGH FLOW AND INCREASED EFFICIENCY

The Outlaw is ready to increase your productivity.

- Pump up to 2,900 GPM: 455+ horsepower engine configurations are available to choose the power you need for your operation. Choose from a range of pumps that match your operation's flow rate and manure consistency.
- The high-performance 15" AR 400 BF submersible pump or 18" white iron Bazooka Farmstar submersible pump features a heavy-duty bearing housing with no mechanical seal for easy maintenance.

### EASY TO MANEUVER BOOM WITH INTEGRATED PLUMBING

The 32' boom has maneuverability and accurate control in mind with its triple-section boom design. The 8" plumbing integrated through the boom is a key upgrade, greatly enhancing ease of use and operational efficiency by minimizing external hoses and drastically reducing setup time.

### AGITATE, PUMP, OR BOTH

Add optional dual, rotating agitation nozzles to provide agitation while pumping. Keep one or both nozzles open while pumping to continue agitation.

### NEXUS PUMP CONTROL COMPATIBILITY

Nexus provides real-time pump monitoring for off-site pump management, which is beneficial for small and large pumping crews alike. Operate your pumps from anywhere you've got an internet connection with the push of a button, using your mobile phone, tablet, or desktop.

# 32' OUTLAW FORCE-FEED TRAILER

## SPECIFICATIONS

### STANDARD

- Gross Weight: 17,000 lbs. (Not including fuel)
- Gooseneck Trailer Length: 27' (Bumper hitch trailer available)
- Gooseneck Trailer Width: 103"
- Approximate Overall Trailer Height: 11' 9" (153")
- Tongue Weight: Full- 2,400 lbs. | Empty- 1,000 lbs.
- Max. Depth: 13' (Below grade) Out 16' from side of trailer
- Max. Reach: 28' (From side of trailer) at ground level
- Max. Slurry Store Height: 15' 6"
- Triple-Fold Boom
- 400-Gallon Steel Fuel Tank w/ Baffle and Sump Area
- Single 25,000 lbs. Tandem Leaf Spring Axles
- [2] 10-Bolt 22.5x13 -3 Offset Used Super Single Tires
- 12,000 lbs. Greaseable, Quick-Change Hubs, and Spindles
- Fenders
- DOT Trailer Lighting
- Rear Hitch Receiver Ready with Trailer Plug
- Rear Axle Electric Over Hydraulic Brakes
- Front Storage Basket Built into the Frame
- Integrated Rear Toolbox with USB Charging Port for Remote
- Discharge Plumbing, 10" Pig Launcher with Chained Cap, and Hydraulic Gate Valves

- [6] LED Flood Lights
- 360° Flood Light Halo [6] LED Flood Lights Included
- Electric Over Hydraulic Pump Backup
- Rear Mounted Controls
- [4] Hydraulic downriggers

### UPGRADES

- [2] 10-Bolt 22.5x13 -3 Offset New Super Singles
- [2] 550 Series 45-22.5 18-Ply Flotation Tires
- Discharge Plumbing with Pig Launcher and Hydraulic Gate valves (6819 Pumps)
- Discharge Plumbing with Pig Launcher and Hydraulic Gate valves (6NHTC Pumps)
- Agitation | Lower Nozzle Only | Includes rotation function and gate valves
- Agitation | Upper and Lower Nozzle | Includes rotation function and gate valves
- 180 CC Hydrostat Motor for 15" Pump | 3000 GPM | 500+ HP Req'd
- NEXUS Engine Control System | Includes 2 Digital Pressure Gauges, Antenna, Stand, and 1 Year Paid Subscription
- Remote Control Package | Includes Boom and Agitation Rotation Functions
- Wireless Boom Remote Control Transmitter Replacement
- 6" Krohne Flowmeter, Display, and [2] 12' Cables
- 8" Krohne Flowmeter, Display, and [2] 12' Cables
- Hydraulic Hookup for Mantis Lagoon Sticks
- Remote Control Charger [1] | Car 12V Micro USB
- Remote Control Charger [1] | Wall 110V Micro USB



[WWW.BAZOOKAFARMSTAR.COM](http://WWW.BAZOOKAFARMSTAR.COM)