

32' RENEGADE 2 AGITATION TRAILER

MAXIMUM VALUE FOR YOUR LIQUID MANURE OPERATION

The 32' Renegade 2 trailer, a cost-effective agitation trailer for any liquid manure management operation, is designed to maximize productivity and efficiency.

- 15" Bazooka Farmstar submersible pump
- 8-inch through the boom plumbing
- Optional integrated load stand
- One-touch remote control tank filling
- Gooseneck or bumper hitch trailer



FEATURES

EFFICIENT AGITATION

- The 32' Renegade 2 comes standard with a 125 CC hydrostat motor, which will reach a GPM of up to 2,900 when paired with a 173 HP engine and 15" Bazooka Farmstar submersible pump.
- The high-performance 15" Bazooka Farmstar submersible pump features a heavy-duty bearing housing with no mechanical seal for easy maintenance.

EASY TO MANEUVER BOOM WITH INTEGRATED PLUMBING

The 32' boom has maneuverability and accurate control in mind with its triple-section boom design. The 8" plumbing integrated through the boom is a key upgrade, greatly enhancing ease of use and operational efficiency by minimizing external hoses and drastically reducing setup time.

OPTIONAL, INTEGRATED 10" DIAMETER LOAD STAND

The 10" diameter load stand increases your loading speed while reducing foaming. Plus, the boom integration keeps operators safer by reducing the equipment needed to do the job.

INCREASE PRODUCTIVITY WITH REMOTE CONTROLS

With our optional rechargeable remote controls, you can place the pump and operate the agitation, pump, force-feed, and tank fill functions all from the push of a button.

32' RENEGADE 2 AGITATION TRAILER

SPECIFICATIONS

STANDARD

- Gross Weight: 13,000 lbs. (Not including fuel)
- Gooseneck Hitch Trailer Length: 27' (324")
- Trailer Width: 103"
- Approximate Overall Trailer Height: 11' 9" (141")
- Tongue Weight: Full- 1,400 lbs. | Empty- 700 lbs.
- 32' Triple Section Boom w/ Nickel-Plated Pins
- Low Mounted Discharge Plumbing
- 15" AR 400 Bazooka Farmstar Submersible Pump
- [2] 3.5" Diameter Agitation Nozzles with Individual Gate Valve Control
- Electric Over Hydraulic Brakes
- Single 25,000 lb Spring Axle
- [2] 10-Bolt 22.5x13 -3" Offset Used Super Single Tires
- [2] 12,000 lbs. Greaseable, Quick-Change Hubs and Spindles
- 200-gallon Steel Fuel Tank with Baffles and Sump
- Integrated Rear Toolbox with USB Charging Port for Remote
- DOT Trailer Lighting
- [6] LED Flood Lights
- 360° Flood Light Halo [6] LED Flood Lights Included

- Built-In Front Storage Basket
- Rear Hitch Receiver Ready with Trailer Plug
- 8" Boom Plumbing
- Manual Hydraulic Agitation and Boom Controls
- Rear Mounted Hydraulic and Engine Controls
- [4] Hydraulic Downriggers, Rear Driver's Side Extends Outward
- Electric Over Hydraulic Pump Backup

UPGRADES

- [2] 10-Bolt 22.5x13 -3 Offset New Super Single Tires
- [2] Flotation Tires - 550 Series 45 - 22.5 18-Ply
- 10" Integrated Loadstand Boom
- Hydraulic Rear-Mounted Hose Reel | Holds 100' of 10" Lay Flat Hose
- 180 CC Hydrostat Motor for 15" Pump
- 8" Krohne Flowmeter, Display and [2] 12' Cables
- Remote Control Package | Includes Boom and Agitation Nozzle Rotation and Fill Functions
- Remote Control | Includes Fill and Agitation Functions
- [1] Remote Control Charger | Car 12V Micro USB
- [1] Remote Control Charger | Wall 110V Micro USB

